

CONNECTOR, 2-Flat Set, 12 IN

INSTALLATION INSTRUCTIONS

READ ALL WARNINGS AND INSTRUCTIONS BEFORE INSTALLATION

⚠ WARNING: The attachment and installation of this product is beyond the control of Winston Products, LLC. Winston Products, LLC is not responsible for the attachment or the installation of this product. Winston Products, LLC is not liable for damages and/or injuries that are the result of improper use/attachment or are the result of use beyond the intended towing application. The liability of this product is limited to the purchase price if it proves to be defective in material and/or workmanship. Any and all warranties, explicit or implied, are void if the product is damaged or worn.

1. Disconnect vehicle power supply.
2. Select the appropriate molded connector required for the installation.
3. Cut the wire to a length that will allow the wire leads to reach the proper circuits.
4. Attach the wire leads to the proper circuits on the vehicle or trailer.

Red Wire – Taillights

White Wire – Ground

NOTE: For proper light function a ground connection must be achieved.

5. Secure any excess wire.
6. Reconnect vehicle power supply.
7. Test lights.

NOTES:

Locate wires by function only. Color coding is not standard among manufacturers.

Apply dielectric grease to terminals to prevent corrosion.

Ensure correct polarity.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.