

Magnetic Towing Light Kit

INSTALLATION INSTRUCTIONS

READ ALL WARNINGS AND INSTRUCTIONS BEFORE INSTALLATION

⚠ WARNING: The attachment and installation of this product is beyond the control of Winston Products, LLC. Winston Products, LLC is not responsible for the attachment or the installation of this product. Winston Products, LLC is not liable for damages and/or injuries that are the result of improper use/attachment or are the result of use beyond the intended towing application. The liability of this product is limited to the purchase price if it proves to be defective in material and/or workmanship. Any and all warranties, explicit or implied, are void if the product is damaged or worn.

NOTE: This product is intended for temporary use to provide tail lamp function as well as stop, turn and hazard indication when towing a vehicle or trailer narrower than 80 inches wide.

INSTALLATION INSTRUCTIONS

1. Place the tow lights in desired position. Magnetic bases should be cleared of any debris that may scratch the mounting surface. Attach the left and right lights on a flat surface as far apart as practical and at an equal distance from the sides of the vehicle trailer being towed. Lights should be placed at the same height. Do not mount lights higher than 6 feet (1829 mm) from the ground or lower than 15 inches (381mm) from the ground. The entire magnet must be touching a steel surface for optimal holding performance. Place red light facing rear and amber light facing forward for optimal visibility at all times.
2. Use a tie wrap to collect any loose cable between the lights. Do not cover or obstruct the lights during operation.
3. Connect the wiring harness from the tow lights to the tow vehicle connector.
4. Verify operation of stop, turn and tail lights before driving on the road. If one or both tow lights do not function, check the connection between the tow vehicle and tow light kit for corrosion.
5. As an added safety precaution, use a bungee or flexible cord to secure the lights to the vehicle or trailer being towed. This will help reduce damage to the lights if they drop off the vehicle due to poor surface connection, wind, inclement weather or large truck traffic causing severe wind shifts.

IF YOU EXPERIENCE ANY PROBLEMS WITH YOUR TOWSMART PRODUCT DO NOT RETURN THE UNIT TO THE RETAILER FROM WHICH IT WAS PURCHASED. INSTEAD, PLEASE CALL 1-844-295-9215 FOR ASSISTANCE WITH ANY PROBLEMS. WARRANTY INFORMATION IS AVAILABLE UPON REQUEST AND CAN BE FOUND ONLINE AT WWW.TOWSMART.COM.



A Winston Products Company
TOWSMART.COM
WINSTON PRODUCTS, LLC.
30339 Diamond Parkway
Cleveland, OH 44139